



SAFETY DATA SHEET

SIKAFLOOR PROSEAL

Buy SIKAFLOOR PROSEAL at
<https://www.spcsupplies.com/products/sikafloor-proseal/>

SIKA - SPC SUPPLIES

Waterproofing Supplies:
<https://www.spcsupplies.com/shop/waterproofing/>

Admixtures and Building Chemical Supplies:
<https://www.spcsupplies.com/shop/admixtures-and-building-chemicals/>

Flooring and wall finishing Supplies:
<https://www.spcsupplies.com/shop/flooring-and-wall-finishing/>

Adhesives, Sealants and Filler Supplies:
<https://www.spcsupplies.com/shop/adhesives-sealants-and-fillers/>

Wood Preservative Supplies:
<https://www.spcsupplies.com/shop/wood-preservatives/>

Sika Concrete Repair Products and Concrete Protection Products:
<https://www.spcsupplies.com/shop/concrete-repair-and-protection/>

Partner Links:

SD Sealants - <https://www.sdsealants.co.uk/>
Bettamix Concrete Manchester - <http://www.bettamixconcretemanchester.co.uk>
Concrete Chemical Admixtures - <http://www.concretechemicaladmixtures.com>

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015



Version 2.1

Print Date 10.08.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikafloor® ProSeal

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company : Everbuild Building products LTD
Site 41, Knowsthorpe Way
Cross Green Industrial Estate
Leeds
LS9 OSW
UK

Telephone : 0113 240 3456

E-mail address : sds@everbuild.co.uk

1.4 Emergency telephone number

Emergency telephone number : 0044 113 240 3456 (office hours only)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3

H226: Flammable liquid and vapour.

Skin irritation, Category 2

H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity - single exposure, Category 3, Respiratory system

H335: May cause respiratory irritation.

Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Chronic aquatic toxicity, Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015



Version 2.1

Print Date 10.08.2015

Hazard statements	:	H226 H304	Flammable liquid and vapour. May be fatal if swallowed and enters air-ways.
		H315 H335 H336 H411	Causes skin irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P210 P280 P241 P273 P235 Response: P304 + P340 P301 + P310 P331 P303 + P361 + P353 Disposal: P501	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/ eye protection/ face protection. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Avoid release to the environment. Keep cool. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

- 918-668-5 Hydrocarbons, C9, aromatics

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Hydrocarbons, C9, aromatics 918-668-5 01-2119455851-35-XXXX [corresponding group CAS	Flam. Liq.3; H226 STOT SE3; H335, H336 Asp. Tox.1; H304	>= 25 - < 50

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1

Print Date 10.08.2015



64742-95-6]	Aquatic Chronic2; H411	
xylene 1330-20-7 215-535-7 01-2119488216-32-XXXX Contains: ethylbenzene <= 25 %	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox.1; H304	>= 25 - < 50
ethylbenzene 100-41-4 202-849-4 01-2119489370-35-XXXX	Flam. Liq.2; H225 Acute Tox.4; H332 STOT RE2; H373 Asp. Tox.1; H304	>= 10 - < 20

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.
Cough
Respiratory disorder
Erythema
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1



Print Date 10.08.2015

Risks : Risk of serious damage to the lungs (by aspiration).
irritant effects

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical

Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015



Version 2.1

Print Date 10.08.2015

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1

Print Date 10.08.2015



Components	CAS-No.	Value	Control parameters *	Basis *
xylene	1330-20-7	STEL	100 ppm 441 mg/m3	GB EH40
		TWA	50 ppm 220 mg/m3	GB EH40
ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40
		STEL	125 ppm 552 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650mmol/mol creatinine (Urine)	Post shift	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015



Version 2.1

Print Date 10.08.2015

exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: No data available
Odour	: No data available
Odour Threshold	: No data available
Flash point	: ca. 32 °C
Ignition temperature	: 465 °C
Lower explosion limit (Vol-%)	: 0,8 %(V)
Upper explosion limit (Vol-%)	: 7 %(V)
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 7,9993 hPa
Density	: ca.0,9 g/cm ³ at 20 °C
Water solubility	: No data available
Partition coefficient: n-	: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1



Print Date 10.08.2015

octanol/water
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s
at 40 °C

Relative vapour density : No data available

Evaporation rate : No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.

Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

Hydrocarbons, C9, aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

xylene:

Acute dermal toxicity : Acute toxicity estimate: 1.100 mg/kg
Method: Converted acute toxicity point estimate

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1



Print Date 10.08.2015

Skin corrosion/irritation

Product:

Remarks: Causes skin irritation.

Serious eye damage/eye irritation

Product:

Remarks: No data available

Respiratory or skin sensitisation

Product:

Remarks: No data available

Germ cell mutagenicity

Product:

Germ cell mutagenicity- Assessment : No data available

Carcinogenicity

Product:

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Product:

Reproductive toxicity - Assessment : No data available

No data available

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics :

Toxicity to algae : 2,6 - 2,9 mg/l, 72 h, Pseudokirchneriella subcapitata (green algae)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015



Version 2.1

Print Date 10.08.2015

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1866

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1



Print Date 10.08.2015

14.2 Description of the goods : RESIN SOLUTION

14.3 Class : 3

14.4 Packing group : III

Classification Code : F1

Labels : 3

Tunnel restriction code : (D/E)

14.5 Environmentally hazardous : yes

IATA

14.1 UN number : 1866

14.2 Description of the goods : Resin solution

14.3 Class : 3

14.4 Packing group : III

Labels : 3

14.5 Environmentally hazardous : yes

IMDG

14.1 UN number : 1866

14.2 Description of the goods : RESIN SOLUTION
(solvent naphtha)

14.3 Class : 3

14.4 Packing group : III

Labels : 3

EmS Number 1 : F-E

EmS Number 2 : S-E

14.5 Marine pollutant : yes

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed
(=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH Information: All substances contained in our Products are

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1

Print Date 10.08.2015



- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t
VOC-CH (VOCV)	: 90 %		
VOC-EU (solvent)	: 90 %		

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of H-Statements

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Sikafloor® ProSeal

Revision Date 10.08.2015

Version 2.1



Print Date 10.08.2015

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	

