

SAFETY DATA SHEET EPOXY PUTTY (BASE COMPONENT)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EPOXY PUTTY (BASE COMPONENT)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

1.3. Details of the supplier of the safety data sheet

Supplier PAREX Ltd
Holly Lane Industrial Estate
Atherstone
Warwickshire
CV9 2QZ
Tel: +44 (0)1827 711755
(Mon-Fri 08:30-16:30)
Fax: +44 (0)1827 711330
sds@parex.co.uk

1.4. Emergency telephone number

Emergency telephone + 44 (0)1827 711755 (Mon-Fri 08:30 - 16:30)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P501 Dispose of contents/ container in accordance with national regulations.
P404 Store in a closed container.

Contains EPOXY RESIN (Number average MW <= 700)

EPOXY PUTTY (BASE COMPONENT)

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EPOXY RESIN (Number average MW <= 700)	30-60%
CAS number: 25068-38-6	EC number: 500-033-5
	REACH registration number: 01-2119456619-26-0000
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	DO NOT induce vomiting. Get medical attention immediately. Immediately rinse mouth and drink plenty of water (200-300 ml).
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.

4.2. Most important symptoms and effects, both acute and delayed

General information	Keep affected person under observation.
Inhalation	May cause irritation.
Ingestion	May cause irritation.
Skin contact	The product is irritating to eyes and skin.
Eye contact	The product is irritating to eyes and skin.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic and corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses.

EPOXY PUTTY (BASE COMPONENT)

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain and absorb spillage with sand, earth or other non-combustible material.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Ensure there is sufficient ventilation in work area.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place.

7.3. Specific end use(s)

Usage description Do not use outside manufacturers specification.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

8.2. Exposure controls

Protective equipment



Eye/face protection Wear eye protection. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection Wear protective gloves.

Hygiene measures Wash at the end of each work shift and before eating, smoking and using the toilet.

Environmental exposure controls Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Clear, yellowish liquid.

Odour Characteristic.

Melting point -5C

EPOXY PUTTY (BASE COMPONENT)

Initial boiling point and range	>200C at 760mm Hg
Relative density	1.13g/ml
Solubility(ies)	Insoluble in water. Soluble in the following materials: Organic solvents.
Viscosity	900 - 1050 mPas

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions May polymerise.

10.4. Conditions to avoid

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Amines.

10.6. Hazardous decomposition products

Hazardous decomposition products In case of fire, toxic gases (CO, CO₂, NO_x) may be formed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	May cause respiratory irritation.
Ingestion	May cause discomfort if swallowed.
Skin contact	Irritating to skin. May cause sensitisation by skin contact.
Eye contact	Irritating to eyes.

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Dangerous for the environment. May cause long lasting harmful effects to aquatic life. Harmful to Fish

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

EPOXY PUTTY (BASE COMPONENT)

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	3082
UN No. (IMDG)	3082
UN No. (ICAO)	3082
UN No. (ADN)	3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN)
Proper shipping name (IMDG)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN)
Proper shipping name (ICAO)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN)
Proper shipping name (ADN)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXIDE RESIN)

14.3. Transport hazard class(es)

ADR/RID class	9
ADR/RID classification code	M6
ADR/RID label	9
IMDG class	9
ICAO class/division	9
ADN class	9

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-A, S-F
ADR transport category	3
Emergency Action Code	•3Z

EPOXY PUTTY (BASE COMPONENT)

Hazard Identification Number 90
(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by QSHE Manager
Revision date 04/09/2018
Supersedes date 07/07/2015
SDS number 21079
Hazard statements in full H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.