

# SAFETY DATA SHEET FRAMEFIX MORTAR (BASE COMPONENT)

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name FRAMEFIX MORTAR (BASE COMPONENT)

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Polyester resin-based mortar - resin component

## 1.3. Details of the supplier of the safety data sheet

Supplier PAREX Ltd

Holly Lane Industrial Estate

Atherstone Warwickshire CV9 2QZ

Tel: +44 (0)1827 711755 (Mon-Fri 08:30-16:30) Fax: +44 (0)1827 711330 sds@parex.co.uk

# 1.4. Emergency telephone number

**Emergency telephone** + 44 (0)1827 711755 (Mon-Fri 08:30 - 16:30)

# SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

#### Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 1 - H372

Environmental hazards Not Classified

# 2.2. Label elements

# **Pictogram**







# Signal word Dar

**Hazard statements** H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (Ears) through prolonged or repeated exposure.

# FRAMEFIX MORTAR (BASE COMPONENT)

Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations. P241 Use explosion-proof electrical/ ventilating /lighting/.../ equipment.

P260 Do not breathe vapours.

Contains UNSATURATED POLYESTER RESIN IN STYRENE

#### 2.3. Other hazards

## SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### **UNSATURATED POLYESTER RESIN IN STYRENE**

60-100%

CAS number: 100-42-5

#### Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361d STOT RE 1 - H372

The full text for all hazard statements is displayed in Section 16.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing.

**Ingestion** DO NOT induce vomiting. Get medical attention immediately.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and

open eyelids widely. If irritation persists: Seek medical attention and bring along these

instructions.

## 4.2. Most important symptoms and effects, both acute and delayed

InhalationHarmful if inhaled. Irritating to respiratory system.Skin contactThe product is strongly irritating to eyes and skin.Eye contactThe product is strongly irritating to eyes and skin.

## 4.3. Indication of any immediate medical attention and special treatment needed

#### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

# 5.2. Special hazards arising from the substance or mixture

# FRAMEFIX MORTAR (BASE COMPONENT)

Specific hazards The product is flammable.

Hazardous combustion

products

When heated, toxic and corrosive vapours/gases may be formed.

## 5.3. Advice for firefighters

Protective actions during

firefighting

Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

#### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Wear

protective clothing as described in Section 8 of this safety data sheet.

#### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains, water courses or onto the ground. Contain spillage with sand,

earth or other suitable non-combustible material.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up No smoking, sparks, flames or other sources of ignition near spillage. Collect spillage in

containers, seal securely and deliver for disposal according to local regulations.

#### 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Wash at the end of each work shift and before eating, smoking and using the toilet.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry and cool place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

#### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limits

#### **UNSATURATED POLYESTER RESIN IN STYRENE**

Long-term exposure limit (8-hour TWA): WEL 100 ppm Short-term exposure limit (15-minute): WEL 250 ppm

Long-term exposure limit (8-hour TWA): WEL 20ppm (Ireland) Short-term exposure limit (15-minute): WEL 40ppm (Ireland)

WEL = Workplace Exposure Limit

#### **UNSATURATED POLYESTER RESIN IN STYRENE (CAS: 100-42-5)**

# FRAMEFIX MORTAR (BASE COMPONENT)

Ingredient comments

Provide good ventilation and local exhaustion in working area Due to the hazardous nature of ingredients, exposure should be minimal.

#### 8.2. Exposure controls

#### Protective equipment





Appropriate engineering

controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist.

**Eye/face protection** Wear eye protection.

Hand protection Wear protective gloves.

Other skin and body

protection

Avoid contact with skin.

**Hygiene measures** Wash at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

**Environmental exposure** 

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

## **SECTION 9: Physical and Chemical Properties**

## 9.1. Information on basic physical and chemical properties

Appearance Liquid.

Odour Aromatic.

Initial boiling point and range >145 C at 760mm Hg

Flash point 31C

Upper/lower flammability or

explosive limits

1.1% to 6.1%

Auto-ignition temperature 490C

9.2. Other information

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

The following materials may react strongly with the product: Peroxides.

10.4. Conditions to avoid

**Conditions to avoid** Keep away from heat, sparks and open flame.

# 10.5. Incompatible materials

## 10.6. Hazardous decomposition products

# FRAMEFIX MORTAR (BASE COMPONENT)

Hazardous decomposition

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or

vapours.

1.5

## SECTION 11: Toxicological information

## 11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (dusts/mists

ATE inhalation (gases ppm) 4,500.0
ATE inhalation (vapours mg/l) 11.0

mg/l)

products

General information Extensive use of the product in areas with inadequate ventilation may result in the

accumulation of hazardous vapour concentrations.

**Inhalation** The liquid may be irritating to eyes, respiratory system and skin. May cause nausea,

headache, dizziness and intoxication.

Skin contact

The product is strongly irritating to eyes and skin.

Eve contact

The product is strongly irritating to eyes and skin.

Target organs Ears

## SECTION 12: Ecological Information

## 12.1. Toxicity

## 12.2. Persistence and degradability

Persistence and degradability The product is biodegradable.

#### 12.3. Bioaccumulative potential

12.4. Mobility in soil

# 12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product is not identified as a PBT/vPvB substance

#### 12.6. Other adverse effects

# SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information** This material and its container must be disposed of as hazardous waste.

**Disposal methods**Dispose of contents/container in accordance with national regulations.

# SECTION 14: Transport information

# 14.1. UN number

UN No. (ADR/RID) 1866 UN No. (IMDG) 1866 UN No. (ICAO) 1866 UN No. (ADN) 1866

# 14.2. UN proper shipping name

# FRAMEFIX MORTAR (BASE COMPONENT)

Proper shipping name

RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

(ADR/RID)

Proper shipping name (IMDG) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

Proper shipping name (ICAO) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

Proper shipping name (ADN) RESIN SOLUTION (CONTAINS UNSATURATED POLYESTER RESIN IN STYRENE)

## 14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

# Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group

ADN packing group

ICAO packing group

# 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

# 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

# SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# FRAMEFIX MORTAR (BASE COMPONENT)

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

**Issued by** QSHE Manager

Revision date 30/08/2018
Supersedes date 22/02/2018

SDS number 21048

Hazard statements in full H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs (Ears) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.