



# TECHNICAL DATA SHEET

## SIKA MULTISEAL 100mm x 10m

Sika MultiSeal is a self-adhesive bituminous sealing tape for the sealing of cracks and joints in many common domestic and commercial situations. It consists of an aluminium foil reinforced by a polyester film and coated with a cold-adhesive bituminous compound.

Buy SIKA MULTISEAL 100mm x 10m at

<https://www.spcsupplies.com/products/sika-multiseal-100mm-x-10m/>

### **SIKA - SPC SUPPLIES**

[Waterproofing Supplies:](#)

<https://www.spcsupplies.com/shop/waterproofing/>

[Admixtures and Building Chemical Supplies:](#)

<https://www.spcsupplies.com/shop/admixtures-and-building-chemicals/>

[Flooring and wall finishing Supplies:](#)

<https://www.spcsupplies.com/shop/flooring-and-wall-finishing/>

[Adhesives, Sealants and Filler Supplies:](#)

<https://www.spcsupplies.com/shop/adhesives-sealants-and-fillers/>

[Wood Preservative Supplies:](#)

<https://www.spcsupplies.com/shop/wood-preservatives/>

## Sika MULTISEAL



Colour	Product Code	Pack Size	Box Qty
LEAD GREY	SKMULTI100	100mm x 10Mtr	3
	SKMIULTI150	150mm x 10Mtr	2
	SKMULTI225	225mm x 10Mtr	2
	SKMULTI300	300mm x 10Mtr	1

### Product Description

Self-adhesive sealing tape made from bitumen rubber compound, protected by a reinforced aluminium film

### Uses

- General repair to existing flashing.
- Roofs including sheet metal work
- Facades
- Broken roof tiles
- Leaking gutters
- Duct work
- Sealing projections through the roof

### Characteristics / Advantages

- Very easy to apply
- Cold applied
- Self-adhesive
- Good adhesion to a wide range of room substrates
- Weatherproof
- Solvent free

### Product Data

Form – Tape

Upper side aluminium dull

Lower side selfa-adhesive black bitumen rubber

### Specific Data

Foil Thickness	50 microns
Adhesive Thickness	1.3mm
Elongation	15%
Tape Strength	3.5 N/mm
Bond Strength To Primed Concrete	3.5 N/mm
Flexibility at -15°C	No cracking
Application Temperature Range	5 to 40°C
Service Temperature Range	-10 to 80°C
Weight	1.4 kg/m <sup>2</sup>

### **Limitations**

- Prime porous surfaces with BITUMEN AND FLASHING PRIMER.
- Do not apply to damp surfaces.
- In cold weather or storage conditions, adhesion may be reduced. Bring up to temperature or heat bitumen adhesive layer with a hot air blower to improve adhesion.

### **Surface Preparation**

All surfaces must be dry, sound and free from oil, grease and dust. Remove all loose material by scraper or wire brush. Porous surfaces, such as concrete or brick, should be primed using BITUMEN AND FLASHING PRIMER and allowed to dry.

### **Application**

Cut to the required length. Peel back approximately 5cm of release carrier and place the tape into position. Continue removing the release carrier whilst firmly placing the tape to avoid unnecessary creasing. Ensure intimate contact and that no air is trapped. Using a small roller ensure that all edges and overlaps are sealed properly. Overlaps should be at least 25mm.

### **Health & Safety**

Consult MSDS for full list of hazards.

### **Storage**

Store in original container in cool dry conditions. Keep away from sources of ignition.

### **Shelf Life**

24 months from date of manufacture in tightly sealed, undamaged containers.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*